112.139

DENTOL EP

75W/85 - 80W - 90 - 120 - 140



Lubrificanti EP per cambi manuali, trasmissioni, riduttori a ingranaggi e differenziali

Extreme pressure Gear Oils –
For Gears and manual gearboxes, transmissions and differentials

(IT)
DESCRIZIONE

Gli oli lubrificanti della serie **Green Star DENTOL EP** sono ricavati da basi minerali altamente selezionate e sono espressamente **formulati per la lubrificazione di cambi e differenziali che richiedono lubrificanti con caratteristiche E.P. (estreme pressioni).**
Le loro prestazioni li rendono particolarmente idonei per tutti i cambi di velocità, differenziali e riduttori di autovetture, autoveicoli industriali e agricoli, dove sia richiesto o consentito l'uso di lubrificanti E.P. per le condizioni di lavoro particolarmente gravose cui sono sottoposti come, per esempio, negli ingranaggi ipoidi o in presenza di urti o sovraccarichi improvvisi.

PROPRIETA' & VANTAGGI

- **Eccezionali caratteristiche E.P. ed antiusura**
- **Alta stabilità termica-chimica**, che ne consente l'uso prolungato anche ad alte temperature, senza che si formino depositi o morchie
- **Elevato indice di viscosità**
- **Ottima resistenza all'ossidazione e alla formazione di schiuma**
- Specifiche caratteristiche **anticorrosive e antiruggine**

(GB)
DESCRIPTION

***Green Star DENTOL EP** gear oils are formulated with a blend of highly selected mineral base oils and specific additives and are **developed for lubrication of gears and differential gears requiring lubricants with E.P. characteristics (Extreme pressures).** Their performance makes them particularly suitable for all gears, differential and gearboxes, equipped on industrial and agricultural vehicles, where it is required a lubricant with E.P. properties for particularly hard working conditions such as hypoid gears or sudden shocks or overloads.*

PROPERTIES & ADVANTAGES

- ***Exceptional features of extreme pressure (EP) and anti-wear (AW).***
- ***High thermal-chemical stability**, allowing long-term use even at high temperatures without forming deposits or sludge*
- ***High viscosity index,** that grant stable performances at any temperature of use*
- *Excellent **resistance to oxidation and foam** formation*
- *Specific **anti-corrosive and anti-rust properties***

F.lli GALBARINI SRL - Via Campestre, 41 - 20091 BRESSO (MI) C.F. e P.Iva 10121490154
Tel. (+39) 02 6101256 Fax (+39) 02 6108042 - info@greenstar.it - www.greenstar.it

PERFORMANCE LEVELS

Performance levels per la gradazione / only for grade SAE 75W/85:
- **API** GL 5, API GL 4
- **FIAT** 9.55550-MZ3
- **MIL**-L-2105 D, MIL-L-2105 E, MIL-PRF-2105 D, MIL-PRF-2015 E
- **SCANIA** STO 1.0
- **ZF** TE-ML 02B, 17 A

Performance levels per la gradazione / only for grade SAE 80W:
- **API** GL 5, API GL 4
- **MB** 235.1
- **MIL**-L-2105 D, MIL-L-2105 E, MIL-PRF-2105 D, MIL-PRF-2015 E
- **SCANIA** STO 1.0

Performance levels per la gradazione / only for grade SAE 90 (SAE 80W/90):
- **API** GL 5, API GL 4
- **CHRYSLER** MS-5644
- **FORD** M2C105-A, FORD M2C154-A
- **IVECO** 18-1805
- **MAN** 341 TYPE Z-2, MAN 341 TYPE M1, MAN 342 TYPE N
- **MB** 235.0 (SAE 80W/90), MB 235.2
- **MIL**-L-2105 D, MIL-L-2105 E, MIL-PRF-2105 D, MIL-PRF-2015 E
- **NATO** CODE O–226
- **NH** 520 B
- **OPEL** B 0401010
- **SCANIA** STO 1.0
- **VW** TL 727, VW TL 726
- **VOLVO** 97310, 97313, 97314
- **ZF** TE-ML 05A, 07A, 12E, 16B, 16C, 17B, 19B, 21A

Performance levels per le gradazioni / only for grades SAE 120 – SAE 140
- **API** GL 5, API GL 4
- **MIL**-L-2105 D, MIL-L-2105 E, MIL-PRF-2105 D, MIL-PRF-2015 E
- **SCANIA** STO 1.0

GRADAZIONI SAE / *SAE VISCOSITY GRADES*

SAE 75W/85 - SAE 80W - SAE 90 (SAE 80W/90) - SAE 120 - SAE 140

F.lli GALBARINI SRL - Via Campestre, 41 - 20091 BRESSO (MI) C.F. e P.Iva 10121490154
Tel. (+39) 02 6101256 Fax (+39) 02 6108042 - info@greenstar.it - www.greenstar.it