815.235

OIL HB 3

Olio per mandrini e bronzine

Vanishing E.P. lubricant

(IT)
DESCRIZIONE

OIL HB 3 è costituito da un olio minerale molto fluido, raffinato con attivazione antiossidante. **E' destinato alla lubrificazione di movimenti rapidi e poco caricati. OIL HB 3** è stato elaborato per la lubrificazione dei mandrini e delle bronzine di macchine utensili che girano a grande velocità, per i meccanismi di precisione, per il materiale tessile e per **tutti i meccanismi idraulici che necessitano di un olio molto fluido.**

APPLICAZIONI

- **Bronzine** con poco gioco e velocità di rotazione elevata
- **Cuscinetti** a rotolamento ad altissima velocità
- Macchine da cucire industriali
- **Asservimenti idraulici** che necessitano di un olio molto fluido

(GB)
DESCRIPTION

OIL HB 3** is composed of a highly fluid mineral oil, refined with antioxidant activation. **It is intended for the lubrication of fast-moving and lightly loaded mechanisms. OIL HB 3** has been developed for the lubrication of spindles and bushings in high-speed machine tools, precision mechanisms, textile equipment, **and all hydraulic systems that require a very fluid oil.

APPLICATIONS

***- Bushings** with minimal clearance and high rotational speed*
***- Rolling bearings** at extremely high speeds*
Industrial sewing machines
***- Hydraulic systems** that require a highly fluid oil*

CARATTERISTICHE MEDIE INDICATIVE *(Non costituiscono specifica)*
AVERAGE PHYSICAL AND CHEMICAL FEATURES (Data are not specifications)

Stato fisico a 20° C *Physical state at 20 ° C*		Liquido *Liquid*
Densità a 20 °C *Density at 20 °C*	Kg/mc	817
Viscosità a 40°C *Viscosity at 40 °C*	mm^2/s	3
Punto di infiammabilità NF EN 22719 *Flash point NF EN 22719*	°C	> 150
Simbolo ISO-L-6743/7 *ISO-L-6743/7 reference*		FD 2

F.lli GALBARINI SRL - Via Campestre, 41 - 20091 BRESSO (MI) C.F. e P.Iva 10121490154
Tel. (+39) 02 6101256 Fax (+39) 02 6108042 - info@greenstar.it - www.greenstar.it