




313.020

RADIATOR CLEANER

Additivo Pulitore Radiatore
Radiator Cleaner Additive



(IT)
DESCRIZIONE

Green Star RADIATOR CLEANER è un prodotto professionale formulato per la **pulizia dei circuiti di raffreddamento ad acqua** di veicoli e di motori fissi.

PROPRIETA' & VANTAGGI

- **Dissolve i depositi calcarei e la ruggine**, scioglie i depositi oleosi e le morchie.
- **Mantiene in sospensione le impurità**.
- Non intacca alcun componente del circuito con cui viene a contatto.
- **Ristabilisce un ottimo scambio termico** nel sistema di raffreddamento.
- **Ripristina il buon funzionamento dei rubinetti e dei termostati**.
- E' compatibile con tutti i tipi di liquidi di raffreddamento a base di glicole.

APPLICAZIONI

- Indicato **per tutti i sistemi di raffreddamento ad acqua** dei veicoli e di motori fissi.
- Da utilizzarsi **quando una temperatura troppo elevata del liquido** sia imputabile ad una perdita d'efficienza del sistema **dovuta a impurità o depositi**.
- Possibile utilizzo **in caso di depositi oleosi** nel circuito di raffreddamento.
- Il trattamento di pulizia del circuito è da effettuarsi **prima della sostituzione del liquido di raffreddamento**.

(GB)
DESCRIPTION

Green Star RADIATOR CLEANER is a professional product formulated for **cleaning the water cooling circuits of vehicles and fixed engines**.

PROPERTIES & BENEFITS

- **Dissolves calcareous deposits and rust**, dissolves oily deposits and sludge.
- **Holds impurities in suspension**.
- **It does not affect any component of the circuit it comes in contact with**.
- **Restores an excellent heat exchange in the cooling system**.
- **Restores the good functioning of the faucets and thermostats**.
- **It is compatible with all types of glycol-based coolants**.

APPLICATIONS

- **Suitable for all water cooling systems of vehicles and fixed engines**.
- **To be used when a too high temperature of the liquid and a loss of efficiency of the system is due to impurities or deposits**.
- **Possible use in case of oil deposits in the cooling circuit**.
- **The circuit cleaning treatment must be done before the old coolant is replaced**.



MODO D'USO

- Con il riscaldamento "aperto", vuotare il circuito.
- Versare il prodotto nel circuito di raffreddamento (non nel vaso d'espansione se non c'è una circolazione forzata).
- Riempire con acqua.
- Lasciare girare il motore per almeno 20/30 minuti od usare il veicolo per max. 200 km.
- Far raffreddare il motore e vuotare il circuito.
- Lavare l'impianto con acqua finchè questa non scorra limpida e riempire con apposito liquido di raffreddamento.
- Controllare che non esistano perdite causate dall'eliminazione del calcare.

- All'occorrenza, aggiungere **Green Star RADIATOR MICRO-SEALER** o **Green Star RADIATOR STOP LEAK**.

- **La dose di 325 ml** tratta circuiti da 5 a 10 litri.

- **1 litro di additivo** tratta circa 20 litri di liquido di raffreddamento.

- **Per circuiti industriali o domestici:** 1 litro di additivo tratta 100 litri

INSTRUCTION FOR USE

- With the "open" heating valve, empty the circuit.
- Pour the product into the cooling circuit (not in the expansion tank if there is no forced circulation).
- Fill the circuit with water.
- Allow the engine to run for at least 20/30 minutes or use the vehicle for max. 200 km.
- Allow the engine to cool and empty.
- Wash the system with water until it flows clear and fill the circuit with a suitable liquid / coolant.
- Check that there are no leaks caused by the elimination of limescale.

- If necessary, add **Green Star RADIATOR MICRO-SEALER** or **Green Star RADIATOR STOP LEAK**.

- **The dose of 325 ml** it deals with circuits from 5 to 10 liters.
- **1 liter of additive** treats about 20 liters of coolant.

- **For industrial or domestic circuits:** 1 liter of additive treats 100 liters